



WHIPPLETREE PRODUCT INFORMATION & SPECIFICATION SHEET

LIME PRODUCTS

Lime PUTTY

DESCRIPTION

Slaked lime in a bucket for mixing with sharp sand to make a traditional render/mortar.

Technical specifications – Lime PUTTY

Colour	Brilliant White
Grade	Slaked from 98% Buxton Quick Lime
Availability	Ex stock
Density	1.3Kg/per litre
Weight	27Kg buckets (20 litres)
Pack size	48 no. buckets per pallet

Warnings/Cautions/Recommendations

We do not give advice on how to use this product. We sell to professional users that have the knowledge of its use.

Always allow plenty of time between coats to ensure the render has fully cured prior to applying the next coat. Lime putty has to dry out fully to achieve its set.

Be very cautious about using Lime Putty during the run up to Winter and during the Winter. It can be damaged by frost many months after use.



WHIPPLETREE PRODUCT INFORMATION & SPECIFICATION SHEET

Commonly Asked Questions

HOW DO YOU MIX AND APPLY LIME PUTTY?

You ask someone that uses Lime products on a regular basis or better still get them to do the job! There is a knack that only experience can teach.

WHAT IS THE DIFFERENCE BETWEEN LIME PUTTY AND HYDRAULIC LIME?

Putty is a paste and Hydraulic is a powder. The main difference is that Putty sets when it has lost all its moisture (i.e. can be a long time in damp, cool conditions) and Hydraulic Lime obtains a 'set' after 15 hours. The end result is very similar.



20 Litre Buckets Of Mature Lime Putty